

Subfloor

Info 2012-01

Avelgem, 30-9-2012

Dear all,

we have added an underlay for Click LVT to our “xtra floor” product range. This underlay has levelling as well as acoustic benefits. You will find hereafter all relevant information you could need.

Product description:

The acoustic system “**XTRAFLOOR Click Underlay**” consists up to 93% natural raw materials on ecological basis and is especially suitable for the floating installation under Click LVT (or other hard floors)

The “**XTRAFLOOR Click Underlay**” product is a high quality walking and impact sound reducing system. The “**XTRAFLOOR Click Underlay**” consists of mineral fillers, vegetable oils and polyurethane binders with a special release foil and single-sided fleece.

Product specifications:

Color: Eco Blue

Thickness: appr. 1,5 mm

Weight: appr. 1,5 kg/m²

Roll size:

- Length: 10 m
- Width: 1 m

Roll weight: 15 kg

Packaging:

- a palletised box with 40 rolls (one-way pallet, size 800x1200)
- box is labelled with Xtra floor logo (see picture)



- rolls are individually packed in PE (PolyEthylene) bags with an installation leaflet in 7 languages (EN, NL, FR, DE, RU, ES, CZ)

xtra floor

Technical specifications:

Sound insulation: ca. 11 dB (DIN EN ISO 140-5, +/- 2 dB)

Fire behavior: Bfl-S1 (EN 13501-1)

IAQ – Indoor Air Quality:

Following IAQ qualifications have been obtained:

- French legislation: A+
- German legislation: Ü-mark

Fitting instructions:

See for separated installation leaflet

Offer:

Description	Article name	# PC/PAL
Click LVT acoustic underlay	XTRAFLOOR Click Underlay	40

Product is available from stock. SAP material number: 1589

Sampling:

A4 samples with complete information label are available from stock.

SAP material number: SM001563

Label example:

The label provides technical specifications for the Xtra Floor Click Underlay in multiple languages. It includes details on thickness, dimensions, weight, acoustic insulation, thermal resistance, fire behavior, and indoor air quality. The label also features several certification logos, including A+ for indoor air quality, Bfl-S1 for fire behavior, and a recycling symbol.

Total thickness / Totale dikte / Epaisseur totale / Gesamtdicke	1,5 mm
Length / Lengte / longueur / Länge Width / Breedte / Largeur / Breite	10 m x 1 m (10m ² per roll)
Total weight / Totaal gewicht / Poids total / Gewicht	15 kg/roll
Acoustic insulation / Kontaktgeluidisolatie / Sonorité à la marche / Trittschallverbesserungsmaß :	ca 11dB
Thermal resistance / Warmtedoorlaatweerstand / Resistance thermique / Wärmedurchlasswiderstand:	0,01m ² K/W
Inflammability / Brandklasse / Classement feu / Brandverhalten:	Bfl - S1
Indoor Air Quality / Kwaliteit van de binnenlucht / Qualité de l'air intérieur / Begrenzung für VOC-Emissionen:	A+



PLEASE INFORM YOUR SALES REPS ACCORDINGLY!!

In case you might have any questions left, do not hesitate asking us.

Regards,
Christ Taveirne