



PODIUM XXL


UK	FR	DE	NL	ES	RU		
Product specification	Information produit	Technische Daten	Technische gegevens	Características del producto	Технические характеристики		
Total thickness	Epaisseur totale	Gesamtstärke	Totale dikte	Espesor total	Общая толщина	EN 428	3,00 mm
Wear layer	Couche d'usure	Nutzschicht	Slijtlaag	Capa de uso	Толщина защитного слоя	EN 429	0,55 mm
Total weight	Poids total	Total Gewicht	Totaal gewicht	Peso total	Общий вес	EN 430	5,70 kg/m²
Surface treatment	Traitement de surface	Oberflächenvergütung	Oppervlakte behandeling	Tratamiento de superficie	Обработка поверхности		PUR
Usage classification	Classification	Klassifizierung	Classificatie	Clasificación de uso de suelo	Клас использования	EN 685	23 - 33
Size (LxW)	Dimension	Abmessung	Afmeting	Dimensión	Размеры (Д x Ш)	EN 427	72" x 9" 182,88 x 22,86 cm
Test results	Résultats des tests	Testergebnisse	Testresultaten	Resultado de pruebas	Результаты испытаний		
Peeling strength of layers	Résistance à la délamination	Trennwiderstand	Apfelsterkte	Resistencia a la delaminación	Сила скрепления слоев	EN 431	> 50N/50 mm
Underfloor heating	Chauffage par le sol	Fußbodenheizung	Vloerverwarming	Suelo radiante	Подогрев пола	EN 12524	suitable - max. 27°
Castor chair	Chaise à roulettes	Rollstuhl	Bureaustoelen	Ruedas de sillas de oficina	Износ воздействия роликов (кресла)	EN 425	pass
Fire resistance	Indice de résistance au feu	Brandverhalten	Vuurbestendigheid	Reacción al fuego	Огнестойчивость	EN 13501-1	Bfl-s1
Chemical resistance	Résistance chimique	Chemikalienbeständigkeit	Chemische bestendigheid	Resistencia a químicos	Стойкость к воздействию химических соединений	EN 423	good
Residual indentation	Poinçonnement	Eindruckverhalten	Weerstand tegen indrukken	Identación residual	Остаточная деформация	EN 433	0,02 mm
Slip resistance	Glissance	Rutschhemmung	Slipweerstand	Resistencia al deslizamiento	Сопротивление скольжению	DIN 51130 EN 13983	R9 class DS
Abrasion resistance	Résistance à l'abrasion	Verschleissverhalten	Slijtweerstand	Resistencia a la abrasión	Стойкость на истирание	EN 660-1	class T
Abrasion class	Classement au test d'abrasion	Abriebklasse	Slijtweerstand classificatie	Clasificación de abrasión	Класс износостойкости	EN 13329	AC4
Dimensional stability	Stabilité dimensionnelle	Dimensionsstabilität	Dimensiestabiliteit	Estabilidad dimensional	Стабильность линейных размеров	EN 434	< 0,25%
Sound reduction	Isolation acoustique	Trittschallschutz	Geluidsreductie	Aislación acustica	Показатель звукоизоляции	EN ISO 717-2 (ΔLw)	5 dB
Light fastness	Résistance à la lumière	Lichtechtheit	Kleurechtheid	Estabilidad al la luz	Цветоустойчивость	ISO 105-B02	> 6
Impact class	Classement au test d'impact	Impact-Klasse	Impactklasse	Clasificacion de impacto	Класс ударпрочности	EN 13229	IC3
Drum noise	Propagation acoustique	Trittschall	Drumgeluid	Propagación acoustica	Показатель воздушного (ударного) шума	EPLF 021029-3:2004	SL70
Warranty	Garantie	Garantie	Garantie	Garantía	Гарантия	Residential Commercial	15 years 10 years



PODIUM XXL



Cathedral Oak / Natural 005B / Art. 0059604 Size 72" x 9" - 182,88 x 22,86 cm



Landscape Oak / Natural 006B / Art. 0059605 Size 72" x 9" - 182,88 x 22,86 cm



Evergreen Oak / Sand 008B / Art. 0059607 Size 72" x 9" - 182,88 x 22,86 cm




Evergreen Oak / Pearl 007B / Art. 0059606 Size 72" x 9" - 182,88 x 22,86 cm



Chapman Oak / Greige 002B / Art. 0059601 Size 72" x 9" - 182,88 x 22,86 cm




Arizona Oak / Beige 012B / Art. 0059611 Size 72" x 9" - 182,88 x 22,86 cm




Chapman Oak / Taupe 003B / Art. 0059602 Size 72" x 9" - 182,88 x 22,86 cm



Scarlet Oak / Dark Brown 010B / Art. 0059609 Size 72" x 9" - 182,88 x 22,86 cm



Scarlet Oak / Espresso 009B / Art. 0059608 Size 72" x 9" - 182,88 x 22,86 cm



Black Oak / Charcoal 001B / Art. 0059600 Size 72" x 9" - 182,88 x 22,86 cm



Black Oak / Vulcano 004B / Art. 0059603 Size 72" x 9" - 182,88 x 22,86 cm



Chapman Oak / Earth 011B / Art. 0059610 Size 72" x 9" - 182,88 x 22,86 cm