

CADIZ

Manufacturing process	Tufted			ISO 2424
Gauge	5/32" Loop			
Pilecomposition	100% Polypropylene (PP)			ISO 2424
Secondary backing	ECO Grip Felt + Felt			ISO 2424
Width	400 cm, 500 cm		± 1%	EN 986
Pile weight	ca. 380 gr/m ²			ISO 8543
Total weight	Felt ca. 1345 gr/m ²	ECO Grip Felt ca. 1420 gr/m ²	± 15%	ISO 8543
Pile height	ca. 3,5 mm			ISO 1765
Total height	Felt ca. 6,0 mm	ECO Grip Felt ca. 6,7 mm	+ 15% / -10%	ISO 1765
Number of knots	ca. 111.540 /m ²		+ 10% / -7,5%	ISO 1763
Fire classification	Felt Efl (EN13501-1)	ECO Grip Felt Efl (EN13501-1)		EN 13501-1
Light fastness	5			105-B02
Wearability	≥ 4			105-X12
Water fastness	≥ 4			105-E01
Thermal resistance	0,120 m ² K/W			ISO 8302
Sound isolation	10,0 dB			ISO 10140
Pattern repeat	44,7 x 38,4 cm			
GUT Nr.	Felt 80F75EEC	ECO Grip Felt 80F75EEC		

Floorsymbols Vlies



Floorsymbols ECO Grip Vlies



Certificates

EN 14041 08 CE Reaction to fire: Efl (EN13501-1) Slip resistance: DS Felt DOP: 1058-115860 Textile Floorcovering EN1307	EN 14041 08 CE Reaction to fire: Efl (EN13501-1) Slip resistance: DS ECO Grip Felt DOP: 1058-115860 Textile Floorcovering EN1307
---	--

