


Lasting Memories 1000 Fusionback

Tuft gauge	1/10 cut pile	ISO 2424
Pilecomposition	100% PP	ISO 2424
Primary Backing	Woven	ISO 2424
Secondary backing	Fushionbacking	ISO 2424
Width	400 cm, 500 cm	± 1% EN 984
Pile Weight	1.000 gr/m ²	ISO 8543
Total weight	Fusionbacking : 1.630 gr/m ²	± 15% ISO 8543
Pile height	6.0 mm	± 2 mm ISO 1766
Total Height	Fusionbacking : 8.0 mm	ISO 1765
Number of knots	161.420 /m ²	-7.5% .+10% ISO 1763
Fire Classification	Efl	EN 13501-1
Use Area	Medium domestic use (22)	EN 1307

Floorsymbols



Certificates

 2024 Betap Tufting B.V. De Blokmat 29 8281 JH Genemuiden EN1307 DOP: 1016#3020 Reaction to fire: Efl Slip resistance: DS Fusionbacking Resilient floor covering to be used within a building	 2024 Betap Tufting B.V. De Blokmat 29 8281 JH Genemuiden EN1307 DOP: 1016#3020-UK Reaction to fire: Efl Slip resistance: DS Fusionbacking Resilient floor covering to be used within a building
--	---